

PO Box 5, Morley, LS27 0QP

Nepshaw Lane South, Morley, Leeds
Tel 0113 253 0241 Fax 0113 252 7029

Head of Laboratory G. Briggs C. Text ATI

Client: AB Ludvig Svensson

Bangatan 8 SE-511 82 Kinna

Sweden

Entry No: 48574-01

Date received: 27/10/2011

Client's Description: Sample of fabric Moss

TEST REPORT

Test Required: Flammability in accordance with IMO A.652 (16)

Pre-treatment: None

Conditioning: A minimum of 96 hours at 50 +/- 20% Relative Humidity, 20 +/- 5°C

Date of Test: 08/11/2011

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Ignition Source	Observations	Result
Smouldering	No flaming or progressive smouldering was observed within one	PASS
cigarette	hour of placement of the cigarettes.	
Butane flame	No flaming or progressive smouldering was observed after	PASS
	removal of the butane flame.	

Note: A	$20-22ka/m^3$	non-fire	retardant	polyurethane	foam v	haeu eev	as the filling	
NOLE. A	20-22KU/III	HOH-III E	retaruant	polyulethane	ioaiii v	vas useu	as the illino	

-----End of Document-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.





G Briggs Head of Laboratory 22 November 2011

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days
 Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.

