

Nepshaw Lane South, Morley, Leeds, LS<sub>27</sub>7JQ Materials Testing Manager: Martin Bowden

t: 0113 5350176

e: Materials.Testing@wyjs.org.uk www.wyjs.org.uk/materialstesting



## **AMENDED TEST REPORT**

Client: AB Ludvig Svensson

Bangatan 8 SE-511 82 Kinna

Sweden

Entry No: 109277-01A

Date received: 11/04/2019

Client's Description: Fabric: Fields

Test Required: Flammability in accordance with IMO 2010 FTP CODE ANNEX 1 PART 7

Pre-treatment: None

**Conditioning:** A minimum of 24 hours at 65+/-5% Relative Humidity, 20+/-5°C

Date Tests Completed: 23/04/2019

Flame application time: 15 seconds

Mode of Flame Application: Edge ignition

The results may not apply to situations where there is restricted air supply or prolonged exposure to large sources of intense heat as in a conflagration.

Face	Warp direction				Weft direction					
Specimen number	1	2	3	4	5	1	2	3	4	5
Flame reached an edge (✓ or X)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
Hole reached an edge (✓ or X)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
Surface Flash (✓ or X)	Χ	Х	Х	Х	Х	Х	Х	Х	Х	Х
Duration of flaming (s)	0	0	0	0	0	0	0	0	0	0
Length of Char (mm)	125	124	100	78	100	74	80	66	86	84
Ignition of Cotton wool (Y/N)	N	N	N	N	N	N	N	N	N	N

Mean Char Length: Warp = 105.4 mm Weft = 78 mm

-----End of Page------

This is hereby certified to be a correct return of the tests made of the items referred to herein

Daniel Young Senior Technologist 23 April 2019

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days.
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- Uncertainty budgets for test methods contained within this report are available on request.
- The results have been obtained for the above test are due to the allowances that have been made based on the uncertainty of the measurement for this test and its associated measurements.

This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.







Client: AB Ludvig Svensson

**Entry No:** 109277-01A



## Comments

On the basis of the tests carried out this sample of fabric meets the performance criteria for curtains and drapes as specified in Clause 3 of IMO 2010 FTP CODE ANNEX 1 PART 7.

## ANNEX

name and address of the manufacturer / supplier, if	AB Ludvig Svensson					
known	Bangatan 8					
	SE-511 82 Kinna					
	Sweden					
type of the material, i.e. curtain, drape, etc	Unknown					
name and/or identification of the product tested	Fields					
description of the sampling procedure, where relevant	Unknown					
mass per unit area	35					
thickness	Unknown					
colour and tone: if the product has a pattern, the	Green					
representative colour shall be described						
quantity and number of any coating	None					
method and quantity of fire retardant treatment	Permanently Flame retardant fibre					
materials of the product such as wool, nylon, polyester,	100% Trevira CS					
etc., and its composite ratio						
composition of weave: such as plain, weave, twilled	Knitted					
density (number/inch): the number of threads per inch in	Warp: 30					
both warp and weft	Weft:36					
yarn number count	Dtex 50					

Amended Report <b>109277-01A</b> . This report supersedes test report <b>109277-01</b> . This amended report has been produced in response to an administration error by WYMTS
End of Document