

Nepshaw Lane South, Morley, Leeds, LS27 7JQ Materials Testing Manager: Martin Bowden t: 0113 5350176 e: Materials.Testing@wyjs.org.uk www.wyjs.org.uk/materialstesting



TEST REPORT

Client:	AB Ludvig Svensson Bangatan 8 SE-511 82 Kinna Sweden
Entry No:	113225
Date received:	27/08/2019
Client's Description:	Fabric: Salt
Test Required:	Flammability in accordance with IMO 2010 FTP CODE ANNEX 1 PART 7
Pre-treatment:	None
Conditioning:	A minimum of 24 hours at 65+/-5% Relative Humidity, 20+/-5°C
Date Tests Completed:	09/10/2019

Flame application time: 15 seconds

Mode of Flame Application: Edge ignition

The results may not apply to situations where there is restricted air supply or prolonged exposure to large sources of intense heat as in a conflagration.

Face	Warp direction					Weft direction				
Specimen number	1	2	3	4	5	1	2	3	4	5
Flame reached an edge (✓ or X)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
Hole reached an edge (✓ or X)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
Surface Flash (✓ or X)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х
Duration of flaming (s)	0	0	0	0	0	0	0	0	0	0
Length of Char (mm)	53	87	70	62	59	55	85	49	60	50
Ignition of Cotton wool (Y/N)	Ν	N	N	N	N	N	Ν	N	Ν	N

Mean Char Length: Warp = 66.2mm Weft = 59.8mm

Comments

On the basis of the tests carried out this sample of fabric meets the performance criteria for curtains and drapes as specified in Clause 3 of IMO 2010 FTP CODE ANNEX 1 PART 7.

-----End of Page-----

This is hereby certified to be a correct return of the tests made of the items referred to herein

Daniel Young Senior Technologist 09 October 2019

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days. * *
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation. Uncertainty budgets for test methods contained within this report are available on request.

* * The results have been obtained for the above test are due to the allowances that have been made based on the uncertainty of the measurement for this test and its associated measurements.

This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.







Client: AB Ludvig Svensson

Entry No: 113225



ANNEX

name and address of the manufacturer / supplier, if	AB Ludvig Svensson					
known	Bangatan 8					
	SE-511 82 Kinna					
	Sweden					
type of the material, i.e. curtain, drape, etc	Curtain					
name and/or identification of the product tested	Salt					
description of the sampling procedure, where relevant	Unknown					
mass per unit area	190 gsm					
thickness	Unknown					
colour and tone: if the product has a pattern, the	Blue					
representative colour shall be described						
quantity and number of any coating	Permanently flame retardant fibre					
method and quantity of fire retardant treatment	Unknown					
materials of the product such as wool, nylon, polyester,	100% Trevira CS					
etc., and its composite ratio						
composition of weave: such as plain, weave, twilled	Unknown					
density (number/inch): the number of threads per inch in	Warp: 18 tr Weft: 17 tr					
both warp and weft						
yarn number count	Nm 15/2 & Nm 27/2					

-----End of Document------

