

TEST REPORT: 4789248387.2

APPLICANT

- Name: AB Ludvig Svensson
- Address: Bangatan 8 Kinna, 511 54 Sweden

Product: ART. POPPY - UPHOLSTERY FABRIC

DATE Report issue:

27/11/2019

Order number: 13121001

REFERENCE STANDARD

UPHOLSTERED FORNITURE: SMOULDER RESISTANCE OF MATERIALS: CALIFORNIA TECHNICAL BULLETIN 117-2013 SECTION 1

Please find attached the test report N. 19-62517 formed by 3 pages.

Laboratory Manager Matteo Longoni

Note: any copy, even partial, of this report, and any change or alteration to it are strictly forbidden. The test results listed in this report are relevant only for the tested sample. Sampling performed by the customer.

Page 1 of 1



TEST REPORT

UL INTERNATIONAL ITALIA SRL

LAB NO: (IT) 19.62517

Via delle Industrie nr 1 20061 Carugate
 DATE IN:
 18/11/2019

 DATE OUT:
 25/11/2019

 PAGE:
 1 OF 3

ATTN:

Sample Description:		ART. POPPY - UPHOLSTERY FABRIC		
Color:	NOT CLAIMED		Item:	//
Labeled Fiber Content:		100% TREVIRA CS		





Requested Test:	UPHOLSTERED FORNITURE: SMOULDER RESISTANCE OF MATERIALS: CALIFORNIA TECHNICAL BULLETIN 117-2013 SECTION 1
-----------------	---

Laboratory Supervisor Giovanni Moro

REMARKS

- 1. This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our written permission.
- 2. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted.
- 3. Our report includes all the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report; provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.
- 4. Information contained in this report will be sent to the final client according to the procedure established in his manual or for Lab Procedure.
- 5. The client is responsible for the sampling, the shipment and the delivery of the sample.



Testing date:

From: 18/11/2019

To: 25/11/2019

UPHOLSTERED FORNITURE: SMOULDER RESISTANCE OF MATERIALS

METHOD

TEST

CALIFORNIA TECHNICAL BULLETIN 117-2013 SECTION 1

COVER FABRIC TEST

TEST SAMPLE	CHAR LENGTH (mm)	TRANSITION TO OPEN FLAMING	THE SAMPLE CONTINUES TO SMOULDER AFTER 45 MINUTES TEST DURATION
1.	22	NO	NO
2.	22	NO	NO
3.	22	NO	NO

CONCLUSION: THE COVER FABRIC PASSES THE TEST

PASS / FAIL CRITERIA

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:

a) The mock-up test specimen continues to smolder after the 45 minute test duration;

b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08a⁻) of more than 1.8 inches (45 mm) develops on the cover fabric.

c) The mock-up test specimen transitions to open flaming.

- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

END OF REPORT